




























Keylock Switches						
Series	Head Shape	Illustration	Two Position		Color	Page No.
ADP16K Series (IP40 plug-in)	Standard		Alternate	A  ADP16K4-AR0-1A	■	39-41
				C  ADP16K4-AR0-1C		
				E  ADP16K4-AR0-1E		
				F  ADP16K4-AR0-1F		
				U  ADP16K4-MR0-1U		
	Square		Alternate	A  ADP16K4-AS0-1A	■	39-41
				C  ADP16K4-AS0-1C		
				E  ADP16K4-AS0-1E		
				F  ADP16K4-AS0-1F		
				U  ADP16K4-MS0-1U		
	Rectangular		Alternate	A  ADP16K4-AT0-1A	■	39-41
				C  ADP16K4-AT0-1C		
				E  ADP16K4-AT0-1E		
				F  ADP16K4-AT0-1F		
				U  ADP16K4-MT0-1U		
	Flange		Alternate	A  ADP16K4-AA0-1A	■	39-41
				C  ADP16K4-AA0-1C		
				E  ADP16K4-AA0-1E		
				F  ADP16K4-AA0-1F		
				U  ADP16K4-MA0-1U		

Buzzer					
Series	Head Shape			Color	Page No.
	Round	Square	Rectangular		
ADP16B Series (IP40)				■	44-46
	ADP16B4-0R0-0140	ADP16B4-0S0-0140	ADP16B4-0T0-0140		

**DESCRIPTION**

- \* Multiple designs to fit with different panel with options for continuous or intermittent tone.
- \* Available Size : Rectangular 18x24 mm  
Square 18x18 mm  
Round diameter : ~18mm
- \* IP 40 protection degree enable the device to be used in equipments of various fields.
- \* The sound pressure 80 db at a distance of 0.1m.
- \* Approvals: UL/CUL/VDE/CE pending

**SPECIFICATIONS**

<b>Rated Voltage</b>	DC12~24V	<b>Terminal</b>	Soldering type
<b>Rated Current</b>	min100mA~max3A	<b>Wire Range</b>	1x1.5mm <sup>2</sup> max
<b>Electrical Life</b>	1000hr(continuous tone)	<b>Cable Range</b>	2x0.75mm <sup>2</sup> /1x1.0mm <sup>2</sup> Max
<b>Sound Pressure</b>	80dB(continuous tone)	<b>Storage Temperature</b>	-40°C~+70°C
<b>Sound Frequency</b>	2±0.5KHzr	<b>Operating Temperature</b>	-25°C~+55°C
<b>Flickering Cycle</b>	55cycles±10%(Intermittent tone)	<b>Degree of Protection</b>	IP40

## ORDER INFORMATION

MODEL FORMAT ADP16B4-0**1**0-0**2**40

### **1** HEAD SHAPE

- R : ROUND
- S : SQUARE
- T : RECTANGULAR

### **2** VOICE

- 1 : CONTINUOUS TONE
- 2 : INTERMITTENT TONE

### CURRENT RATING

DC 12-24V





unit: mm


SHAPE			
DIMENSIONS	Ø 18	18x18	18x24

**HEAD SHAPE**


ADP16B4-0R0-0140






ADP16B4-0S0-0140



ADP16B4-0T0-0140



**MOUNTING DIMENSIONS**



Panel Thickness 0.5 To 5.0