



MPE120 PCB Connector, Header (wave soldering)



MPE120-762



MPE120-016



DIMENSIONS/POSITIONS

| DIMENSIONS/POSITIONS | | MPE120-762 | MPE120-016 |
|----------------------|-----------------------|--------------------|-----------------|
| 間距 | Pitch | 7.62mm | 10.16mm |
| 位數 | Poles | 2 ~ 12Poles | 2 ~ 8Poles |
| 塑膠本體 | Housing Material | PBT | PA 66 |
| 端子 | Contact | Copper, Tin Plated | Ag Plated |
| PCB孔徑 | PCB Hole Diameter | 1.3mm | 1.9mm |
| 環境作業溫度 | Operating Temperature | -40°C to +120°C | -40°C to +105°C |

TECHNICAL DATA

| | | | |
|---|--------------------------------|------|------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | | |
| 額定電流 I _n | Nominal Current I _n | 30A | 66A |
| 額定橫截面 | Nominal Cross Section | - | - |
| 最大負載電流 | Maximum load current | 30A | 66A |
| 絕緣材料 | Insulating Material | PBT | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 300V | 300V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 30A | 66A |

