


## Features of Spring Clamp Ground Terminal Blocks



### SPE 1.5










## Features of Spring Clamp Ground Terminal Blocks


- Vibration proof grounding
- Space-saving design / Front connection.
- Easy to operate, fast wiring installation with top wire entry.
- Corrosion-proof terminal points.
- Easy for the extension of terminal connection.
- Ease of handling and safe connection.
- Low contact resistance.
- Easy mounting and dismounting from the terminal rail.

### 彈片接地型接線座之特性


- 具有抗震及接地之效果
- 節省空間之設計 / 前緣導線連接方式
- 操作簡便且快速的導線安裝方式 ( 頂部進線 )
- 抗腐蝕性佳 ( 使用良好的金屬材料 )
- 容易擴充及延伸性佳
- 操作簡便且連結處安全性高
- 低接觸電阻
- 接線座從軌道上安裝及拆卸容易

Specifications (產品規格)	1.5 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	
UL	AWG16-28	
CSA	AWG16-28	
IEC	0.2-1.5 mm <sup>2</sup>	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9mm	
Material/Available Color (材質顏色)	●	
Rail Dimensions (導軌尺寸)	T / W / H (mm)	
For TS35x7.5 	4x52x34.5	
For TS35x15 	4x52x42	
Accessories (附件)	Cat. No.	Qty.
End Bracket (終端擋板) 	SEW35	50
End Plate (擋板) 	SEP15	50
Comb Link (邊接式聯接件) 	SQV1.5/2	50
	SQV1.5/3	50
	SQV1.5/4	50
Marking Tags (標記號) 	W3 W3Z W3K	500
Tool (工具) 	DS2	


SPE 1.5/3



SPE 1.5/4




SPE 2.5




Specifications (產品規格)	1.5 mm <sup>2</sup>		1.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	AWG 16-28		AWG 16-28		cUL <sup>®</sup> US AWG 12-28	
CSA	AWG 16-28		AWG 16-28		AWG 12-28	
IEC	0.2~1.5mm <sup>2</sup>		0.2~1.5mm <sup>2</sup>		800V/24A/0.2~2.5mm <sup>2</sup>	
Insulating impulse voltage withstand /Pollution degree (額定衝擊電壓 /污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9mm		8-9mm		8-9mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	4x62.5x34.5		4x73x34.5		5 x 53 x 35.5	
For TS35x15	4x62.5x42		4x73x42		5 x 53 x 43	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板)	SEP16	50	SEP17	50	SEP 1	50
Comb Link (連接式聯接件)	SQV1.5/2	50	SQV1.5/2	50	SQV 2.5/2	50
	SQV1.5/3	50	SQV1.5/3	50	SQV 2.5/3	50
	SQV1.5/4	50	SQV1.5/4	50		
MarkingTags (標記號)	W3 W3Z W3K	500	W3 W3Z W3K	500	W5 W5Z W5K	500
Tool (工具)	DS2		DS2		DS3	


### SPE 2.5/3



### SPE 2.5/4




### SPE 4




Specifications (產品規格)	2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>		4 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	c  AWG 12-28		c  AWG 12-28		c  AWG 12-28	
CSA	AWG 12-28		AWG 12-28		AWG 12-28	
IEC	0.2-2.5mm <sup>2</sup>		0.2-2.5mm <sup>2</sup>		0.2-4mm <sup>2</sup>	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9 mm		8-9mm		9-10mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	5 x 64 x 35.5		5 x 75 x 35.5		6 x 59 x 36.5	
For TS35x15	5 x 64 x 43		5 x 75 x 43		6 x 59 x 44	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板)	SEP 2	50	SEP 3	50	SEP 4	50
Comb Link (連接式聯接件)	SQV 2.5/2	50	SQV 2.5/2	50	SQV 4/2	50
	SQV 2.5/3	50	SQV 2.5/3	50	SQV 4/3	50
MarkingTags (標記號)	W5 W5Z W5K	500	W5 W5Z W5K	500	W6 W6Z W6K	500
Tool (工具)	DS3		DS3		DS3	


SPE 4/3









SPE 4/4




SPE 6




Specifications (產品規格)	4 mm <sup>2</sup>		4 mm <sup>2</sup>		6 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	cUL <sup>us</sup> AWG 12-28		cUL <sup>us</sup> AWG 12-28		cUL <sup>us</sup> AWG 10-24	
CSA	AWG 12-28		AWG 12-28		AWG 10-24	
IEC	0.2~4mm <sup>2</sup>		0.2~4mm <sup>2</sup>		0.2~6mm <sup>2</sup>	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9 mm		9-10 mm		12-13 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5 	6 x 73.5 x 36.5		6 x 86 x 36.5		8 x 74.5 x 40	
For TS35x15 	6 x 73.5 x 44		6 x 86 x 44		8 x 74.5 x 47.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板) 	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板) 	SEP 5	50	SEP 6	50	SEP 7	50
Comb Link (連接式聯接件) 	SQV 4/2	50	SQV 4/2	50	SQV 6/2	50
	SQV 4/3	50	SQV 4/3	50	SQV 6/3	50
MarkingTags (標記號) 	W6 W6Z W6K	500	W6 W6Z W6K	500	W6 W6Z W6K	500
Tool (工具) 	DS3		DS3		DS4	


SPE 6/3



SPE 10




SPE 10/3




Specifications (產品規格)	6 mm <sup>2</sup>	10 mm <sup>2</sup>	10 mm <sup>2</sup>
<b>Technical Data (技術參數)</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>
UL	AWG 10-24	AWG 8-24	AWG 8-24
CSA	AWG 10-24	AWG 8-24	AWG 8-24
IEC	0.2~6mm <sup>2</sup>	0.2~10mm <sup>2</sup>	0.2~10mm <sup>2</sup>
Insulating impulse voltage withstand /Pollution degree (額定衝擊電壓 /污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	12-13 mm	15-16 mm	15-16 mm
Material/Available Color (材質顏色)			
<b>Rail Dimensions (導軌尺寸)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>
For TS35x7.5	8 x 93 x 40	10 x 78 x 42.5	10 x 97.5 x 42.5
For TS35x15	8 x 93 x 47.5	10 x 78 x 50	10 x 97.5 x 50
<b>Accessories (附件)</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>
End Bracket (終端擋板)	SEW35    50	SEW35    50	SEW35    50
End Plate (擋板)	SEP 8    50	SEP 9    50	SEP 10    50
Comb Link (連接式聯接件)	SQV 6/2    50	SQV 10/2    50	SQV 10/2    50
	SQV 6/3    50	SQV 10/3    50	SQV 10/3    50
MarkingTags (標記號)	W6 W6Z W6K    500	W6 W6Z W6K    500	W6 W6Z W6K    500
Tool (工具)	DS4	DS5	DS5



### SPE 16



### SPE 16/3



### SPE 35



Specifications (產品規格)	16 mm <sup>2</sup>		16 mm <sup>2</sup>		35 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	UL <sup>®</sup> AWG4-16		AWG4-16		AWG2-12	
CSA	AWG4-16		AWG4-16		AWG2-12	
IEC	1.5~16mm <sup>2</sup>		1.5~16mm <sup>2</sup>		2.5~35mm <sup>2</sup>	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	16-17 mm		16-17 mm		25 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	12.2x82.5x51		12.2x107.8x51		16x100x59	
For TS35x15	12.2x82.5x58.5		12.2x107.8x58.5		16x100x66.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW 35	50	SEW 35	50	SEW 35	50
End Plate (擋板)	SEP 12	50	SEP 12	50	SEP 14	50
Comb Link (邊接式聯接件)	SQV 16/2	50	SQV 16/2	50	SQV 35/2	50
MarkingTags (標記號)	W6	500	W6	500	W6	500
Tool (工具)	DS5		DS5		DS6	